



	TYPICAL EXTERIOR WALL: 2x6 WD STUDS AT 16" O.C. W/ SHEATHING AS SCHEDULED (SEE STRUCT. DWGS.) AND R-19 KRAFT-FACED FIBERGLASS BATT INSULATION U.O.N. GC SHALL PROVIDE 2 LAYERS OF GRADE 'D' 60 lb BUILDING PAPER.		INTERIOR SOUND-RATED WALL: TYPICAL INTERIOR WALL W/ 3-1/2" UNFACED FIBERGLASS BATT INSULATION.
	TYPICAL INTERIOR WALL : 2x4 WD STUDS AT 16" O.C. (2x6 OR 2x8 WHERE NOTED.)		HOODWALL: TYPICAL EXTERIOR WALL WITH 20 GA. S.S. PANEL BEHIND HOOD. REFER TO DETAIL 2/M3.0 FOR EXTENT OF S.S. PANEL.
			DASHED LINE INDICATES INTERIOR SUBSTRATE LOCATION.

WALL SUBSTRATES:  
- DINING ROOM:  
1/2" GYPSUM WALLBOARD FROM T.O. CURB TO 6" ABOVE CEILING HEIGHT U.O.N. SEE 6, 8 & 16 / A6.3. (NOTE: THE CEMENT BOARD SPECIFICATION IS DESIGNED TO ALLOW THE G.C. FLEXIBILITY.)  
- KITCHEN WALLS AND DINING ROOM CLOSET:  
1/2" CEMENT WALLBOARD FROM T.O. SLAB WITH 1/2" CDX PLYWOOD W/FRP SURFACE FINISH TO 6" ABOVE CEILING HEIGHT U.O.N. IF DOUBLE SIDED SHEAR WALL PLYWD IS SPECIFIED THE PLYWOOD SHALL BE CONTINUOUS FROM SILL PLATE TO TOP PLATE. SEE 4, 11 & 20 / A6.3.  
- RESTROOM WALLS:  
5/8" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F. WITH 5/8" HI-IMPACT BRAND XP WALLBOARD, TYPE X CORE FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N. NO SUBSTITUTIONS ALLOWED. FINISH AS SCHEDULED. SEE 11 (SIM), 12 / A6.3.  
- ALL OTHER FRAME WALL CONDITIONS:  
1/2" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F., WITH 1/2" GYPSUM WALLBOARD FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N. FINISH AS SCHEDULED.

<b>WALL LEGEND</b>	<b>E</b>
--------------------	----------

<b>DIMENSIONS:</b> A. ALL DIMENSIONS ARE TO FACE OF STUD U.O.N. REFER TO FOUNDATION PLAN FOR FACE OF CONC. DIMENSIONS. B. DIMENSIONS NOTED AS 'CLEAR' OR 'HOLD' ARE MIN. REQ'D. NET CLEARANCE FROM FACE OF WALL / WAINSCOT FINISH. VERIFY FINAL EQUIPMENT SIZES W/ VENDOR PRIOR TO INT. WALL FRAMING.	
<b>WINDOWS / DOORS:</b> A. SEE SHT. A1.1 FOR WINDOW TYPES AND DOOR SCHEDULE. B. ALL DOOR AND WINDOW OPENING DIMENSIONS ARE TO ROUGH OPENING.	
<b>FINISH SUBSTRATES:</b> A. PROVIDE 1/2" THICK CEMENTITIOUS BD. FROM FLOOR SLAB TO 12" A.F.F. MIN. IN LIEU OF GYP. BD. AT ALL WALLS EXCEPT SHEARWALL SURFACES. U.O.N. B. ALL JOINTS, GAPS OR SPACES LEADING TO ALL HOLLOW OR INACCESSIBLE SPACES SHALL BE SEALED WITH 'NSF INTERNATIONAL' APPROVED SEALANTS. C. ALL BACK OF HOUSE AND OFFICE WALLS SHALL HAVE 1/2" CDX PLYWOOD SUBSTRATE. U.O.N.	
<b>DECOR:</b> A. SEE A2.0 FOR SEATING PLAN AND DETAILS. B. SEE A7.0 FOR FLOOR FINISHES. C. SEE A8.0 - A8.3 FOR WALL FINISHES. D. SEE A7.1 FOR CEILING FINISHES.	
<b>GENERAL:</b> A. PROVIDE THREE FIRE EXTINGUISHERS - (2) 10 lb. BC and (1) 10 lb. ABC - TO COMPLY WITH LOCAL FIRE CODE. LOCATE PER DIRECTION OF FIRE MARSHALL OR LOCAL AUTHORIZING AGENT. B. DRAWINGS ARE BASED UPON WOOD FRAMING. UTILIZATION OF METAL STUDS ON NON-BEARING INTERIOR PARTITIONS, BULKHEADS AND SOFFITS IS ACCEPTABLE. C. ALL ATTACHMENTS MADE THROUGH E.I.F.S. SHALL BE BUSHED TO PREVENT DAMAGE TO THE FINISH, PER 9/A6.2. D. ALL PENETRATIONS THROUGH E.I.F.S. SHALL BE SEALED USING MFRS. APPROVED METHOD.	

**FLOOR PLAN NOTES** **D**

(1) STARTING POINT. ALL SUB-TRADES SHALL USE THIS POINT AS A BEGINNING LAY-OUT (INSIDE FACE OF EXT. WALL STUDS).	(15) START OF CHAIR RAIL.
(2) NO FRP BEHIND <del>W-075</del> WALK-IN COOLER/FREEZER.	(16) CONTINUE CHAIR RAIL AROUND CORNER TO WINDOW JAMB.
(3) PIPE BOLLARD. SEE DETAIL 8/C1.0.	(17) REMOVEABLE ASTRAGAL FROM INSIDE ONLY.
(4) HOOD WALL. SEE WALL LEGEND.	(18) METAL STUDS REQUIRED PER LOCAL CODES.
(5) ELECTRICAL MAIN SWITCH BOARD. REFER TO ELECT. DWGS.	(19) INDICATES WATER HEATER LOCATION. COMES WITH METAL STAND.
(6) CO2 FILL BOX LOCATION.	(20) SPLASHGUARD. SEE DETAIL 9/A6.3. INSTALLATION SHALL BE COORDINATED WITH INSTALLATION OF MOP SINK.
(7) TILE TO CONCRETE METAL THRESHOLD.	(21) ROOF LADDER SEE 7/A6.0.
(8) KEEP CLEAR FOR UTILITIES & SYRUP LINES. SEE DETAIL 14 & 19/A6.4 FOR STUD LAYOUT REQUIREMENTS.	(22) ADD SECOND 2x4 WALL ON KITCHEN SIDE.
(9) MOP SINK. REFER TO SHEET A2.0 & A2.1.	(23) CASED OPENING. REFER TO DETAIL 6/A6.4. DOOR OPTIONAL, REFER TO DOOR SCHEDULE ON A1.1 (DOOR #6).
(10) S.S. CORNER GUARD / WALL CAP, TYP. ALL CORNERS IN BACK-OF-HOUSE FROM REAR WALL TO THE KITCHEN SIDE OF THE SERVICE COUNTER. SEE DETAIL 19/A6.3.	(24) NEW GAS METER.
(11) ELECT. PANELS RECESSED IN 2x6 WALL.	
(12) LIGHTING CONTROL PANEL SURFACE MOUNTED. REFER TO ELECT. DWGS.	
(13) SYRUP LINE CHASE (ABOVE). SEE DETAIL 19/A6.4.	
(14) 6"x6" HORIZONTAL OPENING FOR SYRUP TUBES. COORDINATE WALL PENETRATION WITH COUNTER INSTALLER. SEAL CHASE TO COUNTER. SEE 11/A6.4.	

**KEY NOTES** **B**



2643 fourth ave.  
san diego ca 92103  
619-702-9448

71905 hwy 111 #f  
rancho mirage ca 92270  
760-610-5264



**marks architects 2016**  
ALL REPORTS, PLANS AND DOCUMENTS PREPARED BY MARKS ARCHITECTS SHALL REMAIN THE PROPERTY OF MARKS ARCHITECTS AND IS INTENDED FOR USE FOR THIS SPECIFIC PROJECT ONLY.

PLNG. DEPT. SUBMITTAL	09.29.16
△	
△	
△	
△	
△	
△	
△	
△	
△	

**TACO BELL**  
12975 PALM DR.  
DESERT HOT SPRINGS, CA



**FLOOR PLAN**

**A1.0**