

SITE PHOTOMETRIC PLAN

SCALE: 1/16"=1'-0" 2

LED AREA LIGHTS - PATRIOT® (XPT3)

Crossover LED LIGHTING TECHNOLOGY

US patent 7029456, 7952293, 8082428, 8177306 and CAN 2736757 and MX patent 29631 and ISRL 49679 and AUS 2008312668 and US & Int'l. patents pending

SMARTTEC™ - LSI drivers feature integral sensor which reduces drive current, when ambient temperatures exceed rated temperature.

OCCUPANCY SENSING (IMS) – Optional integral passive infrared motion sensor activates switching of luminaire light levels. High level light is activated and increased to full bright in 1-2 seconds upon detection of motion. Low light level (30% maximum drive current) is activated when target zone is absent of motion activity for ~2 minutes and ramps down (10-15 seconds) to low level to allow eyes time to adjust. Sensor is located on the rear of optical assembly. Sensor optic has a detection cone of approximately 45°. Examples of detection – occurs 30' out from a 30' mounting height pole; occurs 20' out from a 20' mounting height pole.

EXPECTED LIFE - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation location. See LSI web site for specific guidance.

LEDS - Select high-brightness LEDs in Cool White (5000K) or Neutral White (4000K) color temperature. 70 CRI

DISTRIBUTION/PERFORMANCE - Type 3, 5 and FT. Exceptional uniformity with full cutoff creates bright environment at lower light levels. Improved backlight cutoff minimizes light trespass.

HOUSING - One-piece, die-cast aluminum in a multi-radiused, rectangular shape with mounting arm cast in as an integral part of the housing. All hardware is stainless steel or electro-zinc plated steel. Fixture IP65 rated.

OPTICAL UNIT - Clear tempered optical grade flat glass lens sealed to die-cast aluminum door assembly. Secures to housing with stainless steel hinge bracket. Integral over-center latch allows easy tool-less access to driver. Optic provided with catch mechanism to limit door swing. One-piece extruded silicone gasket seals optical assembly against the housing.

MOUNTING - Use with 5" traditional drilling pattern. Integral cast mounting arm is flat for square pole applications. Use round pole adapter (RPPC) to mount to round poles. RPPC must be ordered separately. Extruded 6" arm extension is available (but not required for 90° or 120° mounting configurations).

ELECTRICAL - Two-stage surge protection (including separate surge protection built into electronic driver) meets IEEE C62.41.2-2002, Location Category C. Available with universal voltage power supply 120-277VAC (UE-50/60Hz input) and 347-480VAC. Optional twistlock photocell receptacle is available. Photocell must be ordered separately.

DRIVER - Available in 350mA and 450mA drive currents. (Drive currents are factory programmed). Components are fully encased in potting material for IP65 moisture resistance. Driver complies with FCC 47 CFR part 15 RFI/EMI standard.

OPERATING TEMPERATURE - -40°C to +50°C (-40°F to +122°F)

FINISH - Fixtures are finished with LSI's DuraGrip® polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling.

WARRANTY - LSI LED fixtures carry a limited 5-year warranty.

PHOTOMETRICS - Please visit our web site at www.lsi-industries.com for detailed photometric data.

SHIPPING WEIGHT (in carton) - 56 lbs /25.4 Kg

LISTING - ETL listed to U.S. and Canadian safety standards. Suitable for wet locations. For a list of the specific products in this series that are DLC listed, please consult the LED Lighting section of our website or the Design Lights website at www.designlights.org.

DOE LIGHTING FACTS
Department of Energy has verified representative product test data and results in accordance with its Lighting Facts Program. Visit www.lightingfacts.com for specific catalog strings.

LIGHT OUTPUT - XPT3

		# of LEDs	Lumens (Nominal) Type 3	Type 5	Type FT	Watts (Nominal)
Cool White (5000K)	350mA	128	12500	12100	13300	144
	450mA	128	14600	14400	15800	180
Neutral White (4000K)	350mA	128	11700	11600	12600	144
	450mA	128	13400	13300	14700	180

LED Chips are frequently updated therefore values may increase.

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.

American Innovation American Made · RoHS COMPLIANT · ETL Intertek Wet location (Downlight only) · ARRA Analog compliant · IP65 · DLC Qualified · IDA Dark Sky Friendly · CE

IP65

LSI Industries™ Project Name _____ Fixture Type _____ Catalog # _____

04/30/15
© 2015 LSI INDUSTRIES INC.

TYPE - A

LED PATRIOT® WALL SCONCE (XPWS3)

Crossover LED LIGHTING TECHNOLOGY

US patent 7029456, 8082428 and CAN 2736757 & 2736757 and MX patent 29631 and ISRL 49679 and AUS 2008312668 and US & Int'l. patents pending

SMARTTEC™ -LSI drivers feature integral sensor which reduces drive current, when ambient temperatures exceed rated temperature

ENERGY SAVING CONTROL OPTIONS - DIM- 0-10 volt dimming enabled with controls by others.

OPTIONAL INTEGRAL MOTION SENSOR - Passive infrared motion sensor activates switching of luminaire light levels. High level light is activated when passersby enter target zone and increased to full bright in 1-2 seconds. Low light level (30% of maximum drive current) is activated when target zone is absent of motion activity for 5 minutes and is gradually ramped down (10 seconds) to low level. Sensor detection range 110° horizontal x 93° vertical x 10 meters maximum distance.

EXPECTED LIFE - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation location. See LSI web site for specific guidance.

LEDS - Available with 28 or 48 select high-brightness LEDs in Cool White (5000K) or Neutral White (4000K) color temperature, 70 CRI.

OPTICS/DISTRIBUTIONS - Ultra-high efficiency reflectors provide three distributions. Choose from Wide Throw (WT), Forward Throw (FT) or Wall Wash (WW).

HOUSING - One-piece die-cast aluminum housing is smoothly contoured rectangular shape. Mounting hardware is stainless steel or electro-zinc plated steel. Housing and optical unit are sealed with extruded silicone gasket; supply conductors with molded EPDM bushing.

OPTICAL UNIT - Clear tempered optical-grade flat glass lens sealed to the aluminum optic housing creates an IP65 rated unit. Pressure stabilizing breather allows super-tight protection while preventing cycling from building up internal pressures and vacuums that can stress optical unit seals.

WALL MOUNTING - Galvanized-steel universal wall mounting plate easily mounts directly to 4" octagonal or square junction box. EPDM gasket is supplied to be installed between mounting plate and junction box, sealing junction box from entrance of water. Universal plate permits fixture to be mounted in uplighting (indoor only) or downlighting position.

POLE MOUNTING - XPMA (for square) or XPMAR (for round) allows mounting to poles in single and D180 configurations. Use with 3" reduced drilling pattern.

ELECTRICAL - Two-stage surge protection (including separate surge protection built into electronic driver) meets IEEE C62.41.2-2002, Location Category C. Available with universal voltage power supply 120-277VAC (50/60Hz input) or 347-480VAC.

DRIVER - Available in 350mA and 450mA drive currents (Drive currents are factory programmed). Components are fully encased in potting material for IP65 moisture resistance. Driver complies with IEC and FCC standards. Driver can be easily accessed.

EMERGENCY OPTIONS - Optional integral emergency battery-back-up options are available. BB option operates in 0°C to 60°C ambient temperature and CWBB operates in -20°C to 60°C ambient temperature. When primary AC power failure occurs, both options operate 10 LEDs for minimum of 90 minutes.

OPERATING TEMPERATURE - -40°C to +50°C (-40°F to +122°F)

FINISH - Fixtures are finished with LSI's DuraGrip® polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling.

WARRANTY - LSI LED fixtures carry a limited 5-year warranty.

PHOTOMETRICS - Please visit our web site at www.lsi-industries.com for detailed photometric data.

SHIPPING WEIGHT (in carton) - 30 lbs./13.6Kg

LISTING - ETL listed to ANSI/UL1598, UL8750 and other U.S. and international safety standards. Suitable for wet locations in downlight position. Optional Class 1 Division 2 (groups A, B, C &D) hazardous location rating is available (Select HL option). For a list of the specific products in this series that are DLC listed, please consult the LED Lighting section of our website or the Design Lights website at www.designlights.org.

LIGHT OUTPUT - XPWS3

		Distribution/Lumens (Nominal) Type FT	Type WT	Type WW	Watts
Cool White (5000K)	28	3100	3000	3200	34
	48	5100	5100	5200	55
	28	3700	3600	3800	44
	48	6200	6100	6300	72
Neutral White (4000K)	28	2900	2900	3100	34
	48	4900	4800	4900	55
	28	3500	3500	3700	44
	48	5800	5700	5800	72

LED Chips are frequently updated therefore values may increase.

Also available in traditional light sources

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.

American Innovation American Made · RoHS COMPLIANT · ETL Intertek wet location (downlight only) · ARRA Analog compliant · IP65 · DLC Qualified · IDA Dark Sky Friendly · CE

IP65

LSI Industries™ Project Name _____ Fixture Type _____ Catalog # _____

06/09/15
© 2015 LSI INDUSTRIES INC.

TYPE - B

LIGHT FIXTURE CUT SHEETS

SCALE: NTS 1

MRC ENGINEERING, INC.
Professional Engineers & Lighting Consultants
34300 Gateway Drive, Suite 120
Palm Desert, CA 92211
p: 760-340-9005 f: 760-340-9100

PROJECT:

PULSE INVESTMENT GROUP
CULTIVATION FACILITY
DESERT HOT SPRINGS, CA

REVISIONS

NO.	REVISION	DATE

DATE:	October 26, 2016
DRAWN BY:	GL
CHECKED BY:	FR
PROJECT NO.:	16066

DRAWING TITLE: PHOTOMETRIC PLAN

SHEET NO.: E1.0

File Path & Name: Y:\2016\16066 PI - PULSE INVESTMENT GROUP CULTIVATION FACILITY_WD\E1.0- ELECTRICAL PHOTOMETRIC PLAN.DWG
© MRC ENGINEERING, INC. 2016 Plotted: October 26, 2016 - 11:29 am