



PHOTOMETRIC SITE PLAN

SCALE: 1"=20'-0"

2

LIGHT FIXTURE "A"

VIPER S SERIES		Cat.#	
SMALL VIPER LUMINAIRE		Job	Type
<b>SPECIFICATIONS</b> <p><b>Intended Use:</b> The Beacon Viper luminaire is available with a wide choice of different LED Wattage configurations and optical distributions designed to replace HD lighting up to 400W MH or HPS.</p> <p><b>Construction:</b> • Manufactured with die cast aluminum. • Coated with a polyester finish that meets ASTM B117 corrosion test requirements and ASTM D2222 cracking and loss of adhesion test requirements. • One piece optical cartridge system consisting of an LED engine, LED lamps, optics, gasket and stainless steel bezel. • Cartridge is held together with internal brass standoffs soldered to the board so that it can be field replaced as a one piece optical system. • Two-piece silicone and micro-cellular polyurethane foam gasket ensures a weather-proof seal around each individual LED.</p> <p><b>Electrical:</b> • 100V through 277V, 50 Hz to 60 Hz (UNV), or 347V or 480V input. • Power factor is &gt;0.9 at full load. • All electrical components are rated at 50,000 hours at full load and 25°C ambient conditions per MIL-217F Notice 2. • Dimming drivers are standard, but must contact factory to request wiring leads for purpose of external dimming controls. • Component-to-component wiring within the luminaire may carry no more than 80% of rated load and is certified by UL for use at 600VAC at 90°C or higher. • Plug disconnects are certified by UL for use at 600 VAC, 15A or higher, 13A rating applies to primary (AC) side only. • Fixture electrical compartment shall contain all LED driver components and shall be provided with a push-button terminal block for AC power connections. • The housing is designed for an optional twist lock photo control receptacle. • Ambient operating temperature -40°C to 40°C. • Surge protection - 20KA. • Optional 7-pin ANSI C136.41-2013 twist-lock photo control receptacle available. Compatible with ANSI C136.41 external wireless control devices. • "Leadshut" Circuit - protects luminaire from excessive temperatures. The device shall activate at a specific, factory preset temperature, and progressively reduce power over a finite temperature range. Operation shall be smooth and undetectable to the eye. Thermal circuit is designed to "fall on" allowing the luminaire to revert to full power in the event of an interruption of its power supply, or faulty wiring connection to the drivers. The device shall be able to co-exist with other 0-10V control devices (occupancy sensors, external dimmers, etc.).</p> <p><b>Controls/Options:</b> Available with an optional passive infrared (PIR) motion sensor capable of detecting motion 360° around the luminaire. When no motion is detected for the specified time, the Motion Response system reduces the wattage to factory preset level, reducing the light level accordingly. When motion is detected by the PIR sensor, the luminaire returns to full wattage and full light output. Please contact Beacon Products if project requirements vary from standard configuration. Available with Energen for optional set dimming, timed dimming with simple delay, or timed dimming based on time of night (see www.beaconproducts.com/resources/energen). In addition, Viper can be specified with SiteSync™ wireless control system for reduction in energy and maintenance cost while optimizing light quality 24/7. See ordering information or visit: www.hubbellighting.com/sitesync for more details.</p> <p><b>Installation:</b> • Mounting options for horizontal arm, vertical lap or traditional arm mounting available. Mounting hardware included.</p> <p><b>Finish:</b> • IP3 polyester powder-coat electrostatically applied and thermocured. • IP5 finish consists of a five stage pretreatment regimen with a polymer primer sealer and top coated with a thermoset super TGIC polyester powder coat finish. • The finish meets the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance and resists cracking or loss of adhesion per ASTM D222 and meets surface impacts of up to 160 inch-pounds.</p> <p><b>Listings:</b> • DesignLights Consortium (DLC) qualified, cULC DLC website for more details: <a href="http://www.designlights.org/DLC">http://www.designlights.org/DLC</a>. • Listed to UL1598 and CSA22.2/250.0-24 for wet locations and 40°C ambient temperatures. • cULC rated for ANSI C136.51 high vibration applications with SP2 mounting. • IDA approved.</p> <p><b>Warranty:</b> Five year limited warranty for more information visit: <a href="http://www.hubbellighting.com/resources/warranty">www.hubbellighting.com/resources/warranty</a></p>		<b>BEACON</b> design performance technology	
<b>PRODUCT IMAGE(S)</b>			
<b>DIMENSIONS</b>			
<b>MOUNTING OPTIONS</b>			
<b>CERTIFICATIONS/LISTINGS</b>			

Beacon Products • 2041 58th Avenue Circle East Bradenton, FL 34203 • Phone: 800-345-4928  
Due to our continual efforts to improve our products, product specifications are subject to change without notice.  
© 2015 BEACON PRODUCTS. All Rights Reserved • For more information visit our website: [www.beaconproducts.com](http://www.beaconproducts.com) • Printed in USA VPS-SPEC 11/16

**HUBBELL**  
Lighting

LIGHTING FIXTURE CUT SHEETS

TRAVERSE SERIES		Cat.#	
SURFACE/CEILING/GARAGE		Job	Type
<b>SPECIFICATIONS</b> <p><b>Intended Use:</b> The Traverse luminaire is a wall surface mounted luminaire with a field replaceable LED light engine &amp; optical beam system. Internal components are totally enclosed in rain-tight and corrosion-resistant die cast aluminum housing. The TRV Luminaire is suitable for wet locations.</p> <p><b>Construction:</b> The Traverse luminaire consists of a die cast aluminum two-piece housing. • Die cast main (thermal) housing provides direct heat exchange between the LED light engine and the cool outdoor air by drawing heat through integral heat channels and out to the sculptured and functional luminaire surface. • LED drivers are thermally isolated from the main housing, mechanically attached and heat sinked to the rear housing. • Main housing is designed with heat dissipating fins for LED thermal management without the use of metallic screws, cages, or fans. • Shape of the main housing is designed to prevent debris accumulation and as a bird nesting deterrent. The back and main housings are designed to hinge open for easy mounting and easy access.</p> <p><b>LED/Options:</b> • Optical one piece cartridge system consisting of an LED engine, LED lamps, optics, gasket and stainless steel bezel. • Cartridge is held together with internal brass standoffs soldered to the board so that it can be field replaced as a one piece optical system. • A two-piece die cut silicone and polycarbonate foam gasket ensures a weather-proof seal around each individual LED and allows the Traverse luminaire to be rated for high-pressure hose down applications. • Optical cartridge is secured to the extruded housing with fasteners and a heat pad to ensure thermal conductivity. • Optics are held in place without the use of adhesives and the complete assembly is gasketed for high pressure hose down cleaning. • Cartridge assembly is available in various lighting distributions using TIR designed acrylic optical lenses over each LED.</p> <p><b>Electrical:</b> • 100V through 277V, 50 Hz to 60 Hz (UNV). • Power factor is min 0.92 at full load. • All electrical components are rated at 50,000 hours at full load and 40°C ambient conditions per MIL-217F Notice 2. • Optional 0 to 10 volt dimming drivers are available upon request. • Component-to-component wiring within the luminaire may carry no more than 80% of rated load and is listed by UL for use at 600VAC at 90°C or higher. • Plug disconnects are listed by UL for use at 600 VAC, 15A or higher, 13A rating applies to primary (AC) side only. • Surge protection - 20KA.</p> <p><b>Controls/Options:</b> Traverse is available with an optional passive infrared (PIR) motion sensor capable of detecting motion 360° around the luminaire. When no motion is detected for the specified time, the Motion Response system reduces the wattage down to a factory preset level, reducing light level accordingly. When motion is detected, the luminaire returns to full wattage and full light output. Please contact Beacon Products if project requirements vary from the standard configurations. Available with Energen for optional set dimming with simple delay, or timed dimming based on time of night (see Energen product page for more details: <a href="http://www.energen.com/products/energen">www.energen.com/products/energen</a>). In addition, Traverse can be specified with SiteSync™ wireless control system for reduction in energy and maintenance cost while optimizing light quality 24/7. See ordering information or visit: <a href="http://www.hubbellighting.com/sitesync/">www.hubbellighting.com/sitesync/</a> for more details.</p> <p><b>Installation:</b> • Rear housing (back plate) is designed with various bolt patterns for direct wall mounting or mounting to a recessed 4" junction box. • Rear housing has three integral 3/4" NPT power feed locations (bottom and each side) for surface mounted conduit applications. • After mounting the rear housing to the wall or junction box, the main housing is designed to hinge and hinge closed after connecting the male and female quick connectors. • Mounting design permits a simple retrofit to existing wall luminaires that utilize surface mount or recessed junction boxes.</p> <p><b>Finish:</b> • IP3 polyester powder-coat electrostatically applied and thermocured. • IP5 finish consists of a five stage iron phosphate chemical pretreatment regimen with a polymer primer sealer, oven dry off, and top coated with a thermoset super TGIC polyester powder coat finish. • The finish meets the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance and resists cracking or loss of adhesion per ASTM D222 and meets surface impacts of up to 160 inch-pounds.</p> <p><b>Listings:</b> The luminaire shall bear a CSA label and be marked suitable for wet locations (standard).</p> <p><b>Warranty:</b> Five year limited warranty for more information visit: <a href="http://www.hubbellighting.com/resources/warranty">www.hubbellighting.com/resources/warranty</a></p>		<b>BEACON</b> design performance technology	
<b>PRODUCT IMAGE(S)</b>			
<b>DIMENSIONS</b>			
<b>CERTIFICATIONS/LISTINGS</b>			

LIGHT FIXTURE "B"

LIGHTING FIXTURE CUT SHEETS

SCALE: 1"=20'-0"

1

NR TRADING CULTIVATION FACILITY  
DESERT HOT SPRINGS, CA

REVISIONS:		DATE
NO.	REVISION	DATE

DATE: 03-13-2017  
DRAWN BY: GL  
CHECKED BY: FR  
PROJECT NO.: 17035  
DRAWING TITLE:  
PHOTOMETRIC  
SITE PLAN

SHEET NO.:

E1.0